



Chromebase Mini

*Smaller Surface. Superior Service.
Commercial Grade Chromebase 10" All-in-One Multi-Touch Solution.*

Introducing the Chromebase Mini 10" Multi-touch solution, an ultra-thin and powerful device specifically designed for commercial and corporate usage with a high-touch experience.

The Chromebase Mini is a solid-state interactive solution designed to be extremely reliable and secure, making it ideal for interactive public displays in high traffic environments (i.e. digital signage, POS, kiosk, meeting room management or corporate environments).

Chrome Device Management allows administrators to manage their organization's Chrome devices from a central place. Integrators can also use the signage app of their preference available via the Chrome Web Store to control what's on the screen.

The advantages of the Chromebase Mini:

- A commercial grade multi-touch, all-in-one solution.
- Tough and retail-hardened design for 24/7 operability in public spaces.
- High quality camera and speakers that meet Chrome video conference and Hangouts Requirements.
- Wide viewing angles in landscape and portrait.
- Multiple mounting options: recessed surfaces, wall mounts and kiosks.
- Optional Chrome Device Management to save valuable time, installation cost, programming and maintenance.






29.9 mm



Remove I/O Cover



Audio Combo Jack HDMI Port LAN Port Power Input USB2.0 with BC1.2

Chromebase Mini 10"

Specifications			Front Panel		10.1” native resolution 1280x800 250nits Internal Stereo Digital MIC
Features		Enterprise Grade all-in-one multi-touch solution with Chrome OS. Operating temp <40°C/104°F, shockproof, fanless, and solid state, dust and water resistant front panel, for commercial environments, APAR (AC Power Auto Recovery)	Warranty		The Chromebase Mini comes with a 1 year warranty. Extended warranty optional for 3 years
Operating System		Chrome OS	Rear Panel I/O	USB 2.0 port	support BC1.2 x 3
CPU		Rockchip RK3288C Quad-Core Cortex-A17 turbo up to 1.8GHz		HDMI output	x 1
Graphics		ARM Mali-T764 MP4 GPU @ 600 MHz		RJ45 LAN	x 1 10/100/1000 Mb
Memory		Dual Channel 4GB, LPDDR3		Audio Combo Jack	x 1 (Mic/ earphone)
Chassis		IPX2 Compliant incl. cable cover SECC material - fanless design		Power switch	x 1 (Hidden Type)
Panel & Touch Panel		AHVA Panel 10.1” (1280x800) 250 Nits Support 10 points (PCT Multi Touch) IP54 dust and water protection	Video I/O		FHD Webcam (2MP)
LAN		Gigabit Ethernet [RJ45]	Accessories		User Manual, Warranty and Support Card, Power Cord, Cable Cover (Knock-out Design), On/off pin tool Bundled desktop stand for landscape and portrait mode, cable clamp tie
Audio		Maxim MX98090 Build in stereo digital mic. and speaker	Optional Accessories		VESA wall mount Various bases and mounts
Storage		EMMC 5.0 - 16 GB	VESA		VESA mount: 75 x 75, 50 x 75 Cable clips protect and route cables Flexible cable cover knock-out design
Form Factor	Dimensions (WxHxD)	270 x 179 x 29.9 mm 10.63 x 7.05 x 1.18 inch	Environment	Operating Temperature	0°C ~ 40°C 32°F ~ 104°F
	Weight	1.22 kg / 2.69 lbs		Non-Operation Temperature	-20°C ~ 60°C -7°F ~ 140°F
	Color	Gun-metal black		Relative Humidity	90%@50°C
Networking		Giga LAN Realtek RTL8211E-VB with LED Wi-Fi+ Bluetooth; Wireless 802.11 b/g/n/ac+BT4.0 built-in 2.4/5Ghz Embedded Antenna		IP54 (front) fanless design, IPX2(rear) compliance	

Follow us and get the online service!

AOPEN
Asia Pacific - Great Connection
 aop@aopen.com
 Tel: +886-2-7710-1195
 ext# 1815 or 1810

